

# D50 F series

108mm~430mm

## General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



## Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD50090A12	98	108	134	12	0.22	2800	0.9	32	3.3	0.129	39	320
CD50090A24	98	108	134	24	0.12	2800	0.9	32	3.3	0.129	39	320
CD50190A12	198	208	239	12	0.60	2500	2.5	88	4.3	0.169	46	600
CD50190A24	198	208	239	24	0.40	2500	2.5	88	4.3	0.169	46	600
CD50290A12	298	308	360	12	0.65	2400	3.5	124	4.0	0.157	46	700
CD50290A24	298	308	360	24	0.40	2400	3.5	124	4.0	0.157	46	700
CD50350A12	358	368	420	12	0.75	2300	3.7	131	3.6	0.141	45	770
CD50350A24	358	368	420	24	0.45	2300	3.7	131	3.6	0.141	45	770
CD50420A12	420	430	474	12	0.80	2000	4.0	145	3.2	0.125	46	850
CD50420A24	420	430	474	24	0.50	2000	4.0	145	3.2	0.125	46	850

